

# Mini R-Meter™



Test Well. Build Well.

A rugged hand held field instrument for finding the location, depth and size of reinforcement rebar, post tension, copper and conduit in place



## Product Information

The Mini R-Meter™ is a rugged digital hand-held field instrument for finding the location and depth of reinforcement bars in place.

The Mini R-Meter™ is lightweight, inexpensive, and an easy to use unit to locate rebar. Rebar detection of up to 10" (250mm) can be accomplished when locating large diameter rebar. An easy to read display and a 4 hr battery life are just a few advantages that make the Mini R-Meter one of the most advanced hand held units in the field today. The sensor design allows the end user to quickly and accurately locate and determine concrete cover in corners or hard to reach areas. The system also allows the user to select between Imperial and Metric units. The data can be saved in the instrument for later uploading to a computer. The data is saved in the system with the date and time of the record to help identify prior tests taken. The Mini R-Meter rebar locator is also capable of locating non-ferrous metals.

The eddy current sensor was specifically designed to react with the presence of currents on the outer surface of metal objects. It is uninfluenced by small metal particles in the concrete, whether the concrete is fresh or hardened, wet, or dry. The eddy current sensor also allows the unit to locate both ferrous as well as non-ferrous metals in concrete; thereby finding not only steel reinforcing bars accurately, but also tendons, copper tubing, conduit, and more.

### Detection and Orientation of Rebar

The exact position and orientation of rebar can be measured quickly and accurately. Rebar-free areas can be identified for coring, grinding, resurfacing, or insertion of new machinery mountings.

The instrument can be used to inspect new structures for compliance with specifications as well as old structures under modification.

### Measurement of Concrete Cover

The exact position and orientation of rebar can be measured quickly and accurately. Knowing the size of the rebar, concrete cover can be detected and the distance between the concrete and the surface it will appear in the easy to read display.

### Location of Metals

Locate any metals, as pipe, flues, wire, and sheets embedded in concrete, masonry, or wood. Identification is possible to a depth of 10 inches.

### Location of Pre-Stressed Cables

Locates the position of cables and lost tendon splices in pre or post tension concrete products.

## Applications

- Rebar Locating Detection and Orientation
- Measurement of Concrete Cover
- Concrete Drilling and Sawing
- Repair and Rehabilitation
- Location of Prestressed Cables
- Contractors

## Features & Benefits

- Eddy current design for greater accuracy.
- Single sensor for all depth ranges.
- Daylight visible display
- Locates up to 8" (200mm)
- Economical
- Store Data for Later Upload via USB

**Strength**

**Locators**

**Ultrasonics**

**Corrosion**

**Moisture**

# Mini R-Meter™



Test Well. Build Well.



## Specifications

Operating Temp. Range	-5 C to 45 C (23 deg F to 113 F)
Bar Size Calibration	3/8" to 1 3/8"
Max. Detection Range	10" (No.11 Bar) 250 mm (36 mm Bar)
Power Source	2 AA
Battery Life	4 hours continuous operation
Software	Windows Compatible/ USB Required. HR-8000 and HR-8100 only
Operating Weight	Less than 3.5 pounds (1.60 Kg)

## Sales Numbers

- R-HR-8000** Mini R-Meter
- R-HR-8100** Mini R-Meter w/PC Software



[www.NDTjames.com](http://www.NDTjames.com)  
 email: [info@NDTjames.com](mailto:info@NDTjames.com)  
 800-426-6500 • 773-463-6565  
 3727 N. Kedzie Ave., Chicago, IL 60618-4545, USA

[www.NDTjames.eu](http://www.NDTjames.eu)  
 email: [europe@NDTjames.eu](mailto:europe@NDTjames.eu)  
 +31 (0)548 659032  
 Windmolen 22, 7609 NN Almelo, The Netherlands